

PROFESSIONAL WALKIE-TALKIE



MOTOCOM
MC-250Pro

SBR Walkie-Talkie
Frequency: 245-246MHz

PC PROGRAMMABLE
ELECTRONIC TUNING
TOT & VOX FUNCTION
WATER & DUST PROOF
HIGH CAPACITY BATTERY
SUPER LONG STANBY TIME
LONG RANGE COMMUNICATION

SPECIFICATIONS

GENERAL

Frequency range	245-246MHz	Sensitivity	-122dBm(12dB SINAD)
Power supply	DC 7.2V (Rechargeable Li-ion battery)	Modulation receive bandwidth	5KHz
Number of channels	16 channels	Audio power	0.3W
Impedance	50Ω	Audio distortion	<10%
Antenna	Same frequency single operation	Blocking	≥85dB
Dimensions	110mm x 45mm x 30mm	Intermodulation (W/N)	≥60dB ≥55dB
Weight	SMIT	Adjacent channel selectivity	≥65dB ≥60dB
Output power		Spurious radiation	≥65dB
Modulation mode	16KΦF3E , 11KΦF3E		
Maximum transmission frequency deviation (W/N)	<5K/<2.5KHz		
Spurious radiation	<7μW		
Preamplification characteristic	6dB/per fold		
Emission current	≤ 1.3A		
CTCSS/DCS frequency deviation (W/N)	0.75KHz±50Hz,0.37KHz±30Hz		
Modulation sensitivity	12mV		
Modulation distortion	≤5%		